



MC1000

<http://www.htz.com.tw> 恆錫代理

| Features | Benefits |
|---|--|
| Lightweight and slim form factor | Increases end-user satisfaction and productivity with a comfortable, easy-to-use design |
| High-quality 1D laser scanner | Captures data accurately to improve productivity and operating efficiency |
| Microsoft Windows CE 4.2 | Offers an open, flexible platform for faster and easier application development and porting |
| User-accessible SD Card slot | Offers flexibility to expand storage volume or connect wirelessly |
| Rugged design for light industrial use | Enhances product lifecycle with less downtime: <ul style="list-style-type: none"> • Designed to withstand multiple 4-foot (1.2-m) drops to concrete and up to 500 1.65-foot (0.5-m) tumbles • IP54-rated sealing protects against water and dust for reliable performance in a variety of environmental conditions |
| High-speed Intel XScale processor | Delivers fast performance and processing power for enterprise-level applications |
| 32MB RAM/32MB ROM | Supplies ample storage capacity for applications and data |
| 240 x 240 resolution/2.2-in. monochrome display | Improves productivity with the highest resolution display in this product class |
| Simplified large keypad design | Allows gloved operation and accurate data entry |
| USB 1.1 client | Shortens transfer time for terminal/host data exchange |
| Flexible power source | Permits end user to choose between AAA (included) or Lithium Ion rechargeable batteries, and to change power sources as necessary |
| Device management with Mobility Services Platform (MSP) | Reduces total cost of ownership with accelerated rollout and centralized visibility into mobile devices and applications |

Physical and Environmental Characteristics

| | |
|---------------------------------|---|
| Dimensions: | 6.42 in. H x 2.54 in. W x 1.5 in. D 16.3 cm H x 6.45 cm W x 3.8 cm D |
| Weight (including LiON battery) | 7.23 oz/205 g |
| Display: | TFT-LCD, monochrome, 240 x 240, no touch |
| Backlight: | Electroluminescent (EL) backlight |
| Main Battery: | 3 AAA batteries or 1 rechargeable Lithium Ion 3.7V, 1,800 mAh |
| Expansion Slot: | User-accessible SD slot (with secure cover) |
| Notification: | Scan and charging LEDs |
| Keypad: | 21-key, numeric/shifted alpha |
| Audio: | Beeper |

Performance Characteristics

| | |
|---------------------------|--------------------------------|
| CPU: | Intel XScale 312 MHz processor |
| Operating System: | Microsoft Windows CE 4.2 Core |
| Memory (RAM/ROM): | 32MB RAM/32MB ROM |
| Interface/Communications: | RS-232, USB 1.1 Client |

User Environment

| | |
|--------------------------|---|
| Operating Temperature: | 14° to 122°F/-10° to 50°C |
| Storage Temperature: | -40° to 158°F/-40° to 70°C |
| Humidity: | 0 percent to 85 percent relative humidity, noncondensing |
| Drop Spec: | 4-foot (1.2 m) drops to concrete, 500 1.65-foot (0.5 m) tumbles |
| Sealing Specification: | IP54 |
| Electrostatic Discharge: | Conforms to +/-10 kV air discharge, +/-8 kV direct discharge |

1D Laser Scanner

| | |
|------------------------|---|
| Supported Symbologies: | Interleaved 2 of 5 (ITF), RSS-14/Limited/Expanded, Codabar (NW-7), ITF, MSI Plessey, IATA 2 of 5, Code 39 (standard and full ASCII), Code 93, Code 128, UPCA, UPCE, EAN-13 (WPC), EAN-8, UPC/EAN supplementals, Coupon Code |
| Scan Triggers: | Top panel |

Peripherals and Accessories

| | |
|------------------------------------|---|
| Cradles: | Single-slot USB/RS-232 charging cradle with spare battery well 4-slot USB charging cradle |
| Communication and Charging Cables: | USB communication charging cable, RS-232 communication charging cable, printer cables |
| Vertical-specific attachments: | Modem (connected to single-slot cradle), hand strap |

Application Development

| | |
|--------------------|--|
| Development Tools: | Embedded Visual C++ 4.0, Visual Studio .NET 2003, SDK available through Symbol Developer Zone Web site MCL Rapid Application Development kit |
|--------------------|--|

Regulatory

| | |
|--------------------|--|
| Electrical Safety: | Certified to UL60950, CSA C22.2 No. 60950, EN 60950 |
| EMI/RFI: | CISPR 22 Class B, CISPR 24, FCC Part 15B, EN 55022, EN 55024 |
| Laser Safety: | 21.CFR1040.10 Class II, EN 60825, IEC 60825 Class 2 |

Warranty

The Symbol MC1000 is warranted against defects in workmanship and materials for a period of 12 months from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

NOTICE: Repairs of this product may require the use of Symbol proprietary parts (and/or Symbol proprietary information). Symbol will sell these parts (and provide this proprietary information) only to end-user customers for self-service. It is Symbol's policy not to sell these parts to third-party service providers and not to allow a third-party service provider to act as an ordering or receiving agent for the parts necessary to repair this product. Applicable in the U.S. For all other countries, please contact your Symbol account manager or the local Symbol Customer Service representative in your area for further details.

恆錫股份有限公司



恆錫集團：遍佈全台及大陸
台灣：台北,新竹,台中,台南,高雄
大陸：上海,蘇州,山東,深圳,廈門,天津



Barcodes

HengTzang Co.,LTD

HengTzang Co.,LTD

Barcode

The Best Performing Compact



恆錫股份有限公司
30年老字號,條碼應用先驅
代理銷售全球知名品牌
Sato,HoneyWell,Denso
Motorola,Epson,Sony
各類條碼應用商品
服務品質第一,業界享譽盛名



(條碼機,掃描器,盤點機,收據印表機,軟體系統規劃
標價機,條碼標籤代印服務,碳帶耗材,電腦設備採購)

TEL : (02)2306-8858

FAX : (02)2306-4200

Email : sales@htz.com.tw

http://www.htz.com.tw

地址：108 台北市萬華區柳州街 70 號

